







David Mchedlishvili

(SMART|EDM_lab of TSU)

Work in Tbilisi

GGSWBS'18











JEDI: Charged-Particle EDM Search

Main principle:

 Inject polarized particles into a storage ring:



Apply radial electric field E:



$$rac{\mathrm{d}ec{s}}{\mathrm{d}t}\propto extcolor{d}ec{E} imesec{s}$$

- Non-zero EDM → spin rotation out of the plane
- Track spin rotation → need precise polarimeter










JEDI polarimeter



- LYSO based EM calorimeter for highest energy resolution
- Fast plastic scintillators for particle identification
- FADC based readout for fast data acquisition
- New type of target for unprecedented precision










Final design












First tests at COSY












More pictures...













Current test setup



Goals:

- Demonstrate simultaneous operation of 48+ calorimeter modules
- Test LYSO crystals and SiPMs of different manufacturers
- Identify stable operation of SiPM voltage supplies
- Test unemployed capabilities of DAQ hardware
- Test rotatable detector concept











Opening of SMART|EDM_lab at TSU

29.08.2016



- PhD and Master students involved
- Well equipped and maintained
- Strong cooperation with JEDI collaboration
- Search for and motivate new students

Support:

- Shota Rustaveli National Science Foundation
- Tbilisi State University
- Research Center Jülich (IKP)









What we develop at Tbilisi lab...

- 1. Precise modular power supplies
- 2. Voltage monitoring system
- 3. Data acquisition and online monitoring systems
- 4. New target development...
- 5. Offline data analysis
- 6. Applications...
- **7.** ...










SiPM-based LYSO calorimeter module












SiPM-based LYSO calorimeter module



Current demands:


- Internal radiation + dark current: ~10...30 μA (average)
- Single 300 MeV deuteron hit: ~100 mA (peak)











1mV variation ~ 0.02...0.05 % in gain

Main requirements:

- Modular design
- High output stability
 (temperature, long/short term, low noise)
- Remote on/off capability
- Voltage adjustment

Details: See talk by Otar Javakhishvili...










Current status...



- √ 64 channel supply built
- √ 128 channel voltage monitoring system developed and tested
- ✓ Continues voltage monitored during the run



Details: See talk by Otar Javakhishvili...










Data acquisition and online analysis











Data acquisition and online analysis

Hardware - Based on Struck Sis3316 FADCs

- 16 ch/module
- 250 MS/s, 14 bit
- FPGA-based
- Data buffering, two large memory banks (almost dead time-free)
- Configuration, data acquisition via LAN
- Internal/external triggering
- Integrated CFD feature → Much more precise relative timing (~50 ps!)
- Easily scalable; clock synchronization possible!











Data acquisition and online analysis

Triggering and acquisition schemes:

- 1. Common trigger, sequential module readout
 - Simple event reconstruction
 - No precise timing
 - Big amount of data (empty channels recorded!)
 - Low rate

2. Internal (individual) trigger, sequential module readout

- Precise timing
- Small amount of data
- Moderate rate
- Complex event reconstruction

3. Internal trigger, parallel module readout

- Precise timing
- Small amount of data
- Highest rate!!!
- Most complex event reconstruction

Software must handle all these operation modes...










Data acquisition and online analysis software

Details: See talk by Dito Shergelashvili...












Online data analysis











Summary

- ✓ First version of 64 ch voltage supply built and tested
- ✓ Independent 128 ch voltage monitoring system developed Data taken during recent test-experiments
- Online event reconstruction and data analysis software development follows detector evolution
- Successful Masters thesis defense (by Otar Javakhishvili)

Outlook

- Further development of voltage supplies version 2
- Software development: improve parallelism, implement new tracking system, create GUI interface, ...









Thank you